

<https://www.markazbargh.com/product-category/automation/>

F.R.L Unit 三联件(Three unit)



<https://www.markazbargh.com/product-category/pneumatic-regulator/>

F.R.L Unit 二联件(Two unit)



<https://www.markazbargh.com/product-category/shir-barghi/>

Filter+regulator 调压过滤器



<https://www.markazbargh.com/brand/rih/>

Filter 空气过滤器



<https://www.markazbargh.com/brand/pneu-control/>

Regulator 调压器



<https://www.markazbargh.com/product-category/pneumatic-cylinder/>

Lubricator 油雾器



<https://www.markazbargh.com/product/pneucontrol-smc-type-regulator/>

F.R.L Unit with Auto drain 三联件(Three unit)



型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	压力调整范围 Pressure adjustable range	过滤精度 Filtration	压力表 Pressure gauge	说明 Note
AC2000-01	G1/8	900 L/min	0.15~0.85Mpa	25 μm	Y40-01	压差排水型 Different pressure drain
AC2000-02	G1/4	900 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3000-02	G1/4	1500 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3000-03	G3/8	2000 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC4000-04	G1/2	4000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC4000-06	G3/4	4500 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5000-06	G3/4	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5000-10	G1	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	压力调整范围 Pressure adjustable range	过滤精度 Filtration	压力表 Pressure gauge	说明 Note
AC2010-01	G1/8	900 L/min	0.15~0.85Mpa	25 μm	Y40-01	压差排水型 Different pressure drain
AC2010-02	G1/4	500 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3010-02	G1/4	1700 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3010-03	G3/8	1700 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC4010-04	G1/2	3000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC4010-06	G3/4	3000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5010-06	G3/4	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5010-10	G1	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	压力调整范围 Pressure adjustable range	过滤精度 Filtration	压力表 Pressure gauge	说明 Note
AW2000-01	G1/8	500 L/min	0.15~0.85Mpa	25 μm	Y40-01	压差排水型 Different pressure drain
AW2000-02	G1/4	550 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AW3000-02	G1/4	2000 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AW3000-03	G3/8	2000 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AW4000-04	G1/2	4000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AW4000-06	G3/4	4500 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AW5000-06	G3/4	5500 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AW5000-10	G1	5500 L/min	0.15~0.85Mpa	25 μm	Y50-02	

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	过滤精度 Filtration	使用温度 Operating temperature Range	说明 Note
AF2000-01	G1/8	750 L/min	25 μm	-5~55℃	压差排水型 Different pressure drain
AF2000-02	G1/4	750 L/min	25 μm	-5~55℃	
AF3000-02	G1/4	1500 L/min	25 μm	-5~55℃	
AF3000-03	G3/8	1500 L/min	25 μm	-5~55℃	
AF4000-04	G1/2	4000 L/min	25 μm	-5~55℃	
AF4000-06	G3/4	6000 L/min	25 μm	-5~55℃	
AF5000-06	G3/4	7000 L/min	25 μm	-5~55℃	
AF5000-10	G1	7000 L/min	25 μm	-5~55℃	

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	压力调整范围 Pressure adjustable range	压力表 Pressure gauge
AR2000-01	G1/8	550 L/min	0.15~0.85Mpa	Y40-01
AR2000-02	G1/4	550 L/min	0.15~0.85Mpa	Y40-01
AR3000-02	G1/4	2000 L/min	0.15~0.85Mpa	Y40-01
AR3000-03	G3/8	2000 L/min	0.15~0.85Mpa	Y40-01
AR4000-04	G1/2	4000 L/min	0.15~0.85Mpa	Y50-02
AR4000-06	G3/4	4500 L/min	0.15~0.85Mpa	Y50-02
AR5000-06	G3/4	5500 L/min	0.15~0.85Mpa	Y50-02
AR5000-10	G1	5500 L/min	0.15~0.85Mpa	Y50-02

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	建议用油 Recommended oil	使用温度 Operating temperature Range
AL2000-01	G1/8	750 L/min	ISO VG32 透平1号油	-5~55℃
AL2000-02	G1/4	750 L/min		-5~55℃
AL3000-02	G1/4	1500 L/min		-5~55℃
AL3000-03	G3/8	1500 L/min		-5~55℃
AL4000-04	G1/2	4000 L/min		-5~55℃
AL4000-06	G3/4	6000 L/min		-5~55℃
AL5000-06	G3/4	7000 L/min		-5~55℃
AL5000-10	G1	7000 L/min		-5~55℃

型号 Model	螺纹尺寸 Thread size	最大流量 Max. rated flow	压力调整范围 Pressure adjustable range	过滤精度 Filtration	压力表 Pressure gauge	说明 Note
AC2000-01D	G1/8	900 L/min	0.15~0.85Mpa	25 μm	Y40-01	自动排水型 Auto drain
AC2000-02D	G1/4	900 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3000-02D	G1/4	1500 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC3000-03D	G3/8	2000 L/min	0.15~0.85Mpa	25 μm	Y40-01	
AC4000-04D	G1/2	4000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC4000-06D	G3/4	4500 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5000-06D	G3/4	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	
AC5000-10D	G1	5000 L/min	0.15~0.85Mpa	25 μm	Y50-02	