

Ø100 Standard Bottom Connection Manometers

- Used for pressure measurement of liquids and gases.



Model No: **A 1001**

<https://www.markazbargh.com/product-category/automation/>

Product Specifications

<https://www.markazbargh.com/product-category/hydraulic/>

STANDARD FEATURES

Accuracy Class:	1,6			
Mechanism:	Brass			
Case:	Steel, chrome or black oven painted			
Frame:	Steel, black oven painted, chrome or acrylic			
Connection:	Brass 1/2 BSP (Other size threads on the request)			
Pressure Unit:	Cu Sn 8 Bourdon Tube			
Dial:	Aluminum, black division on white base or white division on black base			
Scale Unit:	bar/psi			
Scale Range:	-1 - 0 bar /psi	0-1 bar /psi	0-16 bar /psi	0-160 bar /psi
	-760..0 Hgmm	0-2,5 bar /psi	0-25 bar /psi	0-250 bar /psi
	-1- +3 bar /psi	0-4 bar /psi	0-40 bar /psi	0-315 bar /psi
	-1-+5 bar /psi	0-6 bar /psi	0-60 bar /psi	0-600 bar /psi
	-1-+15 bar /psi	0-10 bar /psi	0-100 bar /psi	0-1000 bar /psi

<https://www.markazbargh.com/brand/simga/>

TECHNICAL DETAILS

Standard:	EN 837-1
Environment Temperature:	-20...+60°C
Warehouse Temperature:	-40...+70°C
Madde İsi:	Special production is required if used up to 60 ° C for soft solder, up to 100 ° C for hard solder, up to 200 ° C at higher temperatures.

<https://www.markazbargh.com/brand/pneu-control/>

FEATURES ON THE REQUEST

- ½ NPT or other size thread
- Special dial printing
- Stainless Steel Connection and Bourdon Tube
- Stainless and chrome case or frame